










## Conference Microphone System Price List

Conference Microphone				
No.	Product	Mode	Ref Pic	Specification
1	Wireless VHF Conference Microphone System (2 MICs)	CMS-V102		2 Channel VHF mic, VHF transmitter 190MHz~280MHz, Quartz crystal, 2 balanced output and 1 mixed unbalanced output, Support 8 groups or 16 Mics use simultaneously
2	Wireless VHF Conference Microphone System (4 MICs)	CMS-V104		4 Channel VHF mic, VHF transmitter 190MHz~280MHz, Quartz crystal, 2 balanced output and 1 mixed unbalanced output, Support 4 groups or 16 Mics use simultaneously
3	Wireless VHF Conference Microphone System (8 MICs)	CMS-V104		8 Channel VHF mic, VHF transmitter 190MHz~280MHz, Quartz crystal, 2 balanced output and 1 mixed unbalanced output, Support 2 groups or 16 Mics use simultaneously
4	Wireless UHF Conference Microphone System (2 MICs)	CMS-U602		2 Channel UHF mic, UHF transmitter 500MHz~900MHz, PLL synthesized, 2 balanced output and 1 mixed unbalanced output, Support 20 groups or 40 Mics use simultaneously
5	Wireless UHF Conference Microphone System (4 MICs)	CMS-U604		4 Channel UHF mic, UHF transmitter 500MHz~900MHz, PLL synthesized, 2 balanced output and 1 mixed unbalanced output, Support 10 groups or 40 Mics use simultaneously
6	Wireless UHF Conference Microphone System (8 MICs)	CMS-U608		8 Channel UHF mic, UHF transmitter 500MHz~900MHz, PLL synthesized, 2 balanced output and 1 mixed unbalanced output, Support 5 groups or 40 Mics use simultaneously
7	Wired Discussion Microphone System (Chairman & Delegate)	CMS-350M CMS-3504C CMS-3504D		The panel adopts buttons to control speaking mode and the number of speakers, breaking the traditional dial control   The number of speakers: 1, 3, 6 and full opening( 4 forms can be chosen)   6 meeting work mode   It support 60 microphone units,
8	Wired Discussion Microphone System (Chairman & Delegate)	CMS-351M CMS-3515C CMS-3515D		The panel adopts buttons to control speaking mode and the number of speakers   6 meeting work mode   It support 60 microphone units   Built-in telephone coupler input and output port   RS232 interface
9	Digital Conference Microphone System (Chairman & Delegate)	CMS-690M CMS-692C CMS-692D		Discussion   6 meeting work mode   It support 150 microphone units   TCP/IP protocol   RS232 interface   Protocol TCP/IP or RS-232   Short-circuit input for EMC  adjust voice sensitivity and volume  Built-in IC card reader for check-in (sign) function   6 in 4 out video switch matrix