

## Active Bluetooth Wall Mount Speaker BS-1500A BS-1600A



Active wall mount speaker, designed in ABS body, with a 2-way 5 inch/ 6 inch speaker, built-in amplifier rated power 25/35 Watts @ 8Ω, use for home audio system or public address system (pa system). Fast installation wall mounting bracket and angle adjustable. Treble, bass and master volume control, balance phoenix / RCA and 3.5mm input. The speaker also can be used for home audio system. It is durable and practical and very competitive to satisfy medium or high level sound system.

### Features

2-way 5" woofer + 1" tweeter / 6" woofer + 1" tweeter speaker;

Active speaker with built-in amplifier rated power 25/35 Watts, max power 40/50 Watts;

Balanced phoenix input, RCA audio input, sound and tone volume adjustable;

Sensitivity 94±3 dB, 95±3 dB;

Frequency Response 80~18KHz/70~18KHz;

Adjustable wall mount speaker with wall mounting parts;

Strong ABS material body;

Dimension 185x170x250mm/215x200x295mm;

Weight:4.8kg/pair, 10.5kg/pair

### Specification

Model No.	BS-1500A	BS-1600A
Rated Power / Max Power	25W / 40W	35W / 50W
Speaker	2 way 5" + 1" speaker	2 way 6" + 1" speaker
Power Supply	AC 220~240V	
Sensitivity	94±3dB	95±3dB
Frequency Response	80-18KHz	70-18KHz
Mounting Method	Onwall mounting speaker	
Colour	Black / White	
Dimension	185 x 170 x 250 mm	215 x 200 x 295 mm
Weight	4.8 kg / pair	10.5 kg / pair

## Active Bluetooth Wall Mount Speaker BS-8412BT



Active Bluetooth wall mount speaker, made of ABS body and arc design metal grill, with 2-way 4 inch woofer and 1 inch tweeter, rated power 12-15 Watts, use for small rooms or hotel rooms. Fast installation with screws on wall. It is delivers clear sound and practical use at very competitive cost to satisfy medium or high level sound system.

### Features

4" woofer and 1" tweeter;

Rated power 12 Watts, max power 25 Watts;

Input voltage 100 Volt;

Sensitivity  $86 \pm 3$  dB;

Frequency Response 100~18KHz

Mounting speaker on wall with screws;

High quality plastic body;

Dimension 165x268x80mm

Weight:1.5kg

### Specification

Model No.	BS-8412BT
Rated Power / Max Power	12W / 25W (Built-in amplifier)
Speaker	4" woofer + 1" tweeter
Power Supply	220V 50/60Hz
Audio Source	Bluetooth (10-15 meters)
Sensitivity	$86 \pm 3$ dB
Frequency Response	100-18KHz
Mounting Method	Onwall mounting speaker
Colour	Black & White
Dimension	165 x 268 x 80 mm
Weight	2.2 kg

## Active Bluetooth Speaker with Wireless Mic T-243



T-243 is a wall mounting active speaker with a wireless 2.4G mic, 4" speaker drivers handle 30W power of sound. The speaker delivers high quality of human voice, noise sound can be filtered, and clean sound be picked up by microphone.

### Features

4" speaker driver;

Rated power 30 Watts, max power 50 Watts;

GFSK Mode

### Specification

Model No.	T-243
Speaker	4" speaker driver
Power / Max	30W / 50W
Audio Input	RCA input
Input	1 Mic inputs + 1 Audio input
S/N Ratio	> 80dB
Volume Control	Echo & Tone control
2.4G Mode	2402~2482MHz
Sensitivity	91 dB
Transistor Use	Last 6-8 hours per time
Power Supply	220V 50/60Hz (Speaker) 3.7V Li Battery (Transistor)
Wireless Microphone	Handheld or headset

## Active Bluetooth Speaker with Wireless Mic T-30



T-30 is a wall mounting active speaker with a wireless Bluetooth mic, 2 way 5.25" speaker drivers handle 30W power of sound. The speaker delivers high quality of human voice, noise sound can be filtered, and clean sound be picked up by microphone.

### Features

5.25" speaker driver;

Rated power 30 Watts, max power 50 Watts;

Bluetooth communication

### Specification

Model No.	T-30
Speaker	5.25" woofer + 1" tweeter
Power / Max	30W / 50W
Audio Input	RCA input
Output	1 RCA Audio Output
S/N Ratio	> 80dB
Volume Control	Main Volume & Tone control
Sensitivity	90 dB
Transmitter Use	Last 6-8 hours per time
Power Supply	220V 50/60Hz (Speaker) 3.7V Li Battery (Transmitter)
Wireless Microphone	Handheld or headset

## Active Bluetooth Ceiling Speaker HC-B530Z



HC-B530Z is a frameless ceiling speaker with bluetooth receiver.

### **Features**

30W power;

Built-in Bluetooth receiver;

Frameless design

### **Specification**

Model No.	HC-B530Z
Speaker	2 way speaker 5.25" PP +1" silk tweeter
Power	30W
Frequency Response	100Hz~20KHz
Sensitivity	>86 dB
Size	D 214 x 88.9 mm