

## Pendant Speaker HS-615A



Pendant speaker HS-615A, designed in ABS body, with 6 inch speaker driver, rated power 15 Watts, use for commercial audio system or public address system (pa system) of input voltage 100 volt. Fast installation hanging accessories. Black and white color for option. It is durable and practical and very competitive to satisfy medium or high level architecture sound system.

### **Features**

6" speaker driver;

Rated power 15 Watts, max power 30 Watts;

Input voltage 100 Volt;

Sensitivity  $88 \pm 3$  dB;

Frequency Response 120~15KHz

Pendant mounting or hanging;

Strong ABS material body;

Dimension 255x460mm

Weight:2.5kg

### **Specification**

Model No.	HS-615A
Rated Power / Max Power	15W / 30W
Speaker	6" speaker driver
Input Voltage	100V Line
Sensitivity	$88 \pm 3$ dB
Frequency Response	120-15KHz
Mounting Method	Pendant Mounting
Colour	Black / White
Dimension	255 x 460 mm
Weight	2.5 kg

## Pendant Speaker HS-630



Pendant speaker HS-630, designed in ABS body, with 6 inch speaker driver, rated power 30 Watts, use for commercial audio system or public address system (pa system) of input voltage 100 volt. Fast installation hanging accessories. Black and white color for option. It is durable and practical and very competitive to satisfy medium or high level architecture sound system.

### Features

6" speaker driver;

Rated power 30 Watts, max power 60 Watts;

Input voltage 70/100 Volt;

Sensitivity  $92 \pm 3$  dB;

Frequency Response 90~16KHz

Pendant mounting;

Strong ABS material body;

Dimension 380x300mm

Weight:3.6kg

### Specification

Model No.	HS-630
Rated Power / Max Power	30W / 60W
Speaker	6" speaker driver
Input Voltage	100V Line
Sensitivity	$92 \pm 3$ dB
Frequency Response	90-16KHz
Mounting Method	Pendant Mounting
Colour	Black / White
Dimension	380 x 300 mm
Weight	3.6 kg

## Pendant Speaker HS-820



Pendant speaker HS-820, designed in ABS body, with 8 inch speaker driver, rated power 20 Watts, use for commercial audio system or public address system (pa system) of input voltage 100 volt. Fast installation hanging accessories. Black and white color for option. It is durable and practical and very competitive to satisfy medium or high level architecture sound system.

### Features

8" speaker driver;

Rated power 20 Watts, max power 40 Watts;

Input voltage 70/100 Volt;

Sensitivity  $92 \pm 3$  dB;

Frequency Response 80~18KHz

Pendant mounting;

Strong ABS material body;

Dimension 254x2255mm

Weight:2.5kg

### Specification

Model No.	HS-820
Rated Power / Max Power	20W / 40W
Speaker	8" speaker driver
Input Voltage	100V Line
Sensitivity	$92 \pm 3$ dB
Frequency Response	80-18KHz
Mounting Method	Pendant Mounting
Colour	Black / White
Dimension	254 x 2255 mm
Weight	2.5 kg