#### **COMMERCIAL AUDIO SYSTEM**

# **Mixer Amplifier**

PA-500R

The device is compact designed 50W mixer amplifier in 70V, 100V and 8 ohm speaker output, with basic features of volume control for treble, bass, MICs and main.

It has 2 MIC inputs and 2 auxiliary inputs, and 1 line output.

Highlights of the amplifier is integrated long distance volume control via remote up to 10~30 meters, convenient use for sound level adjustment from farther spot.

PA-500R can be set on tabletop or under the table, and wall mounting installation also available with supplied kits.



### Accessories

- Mounting kit
- Antenna
- Remote controller



Various applications for shops, restaurants, gym, offices, factory workshops, multimedia rooms, café or wine bars music or public address sound system.

**Placement** 

The mixer amplifier PA-500R provides different way for placement, either set on table, mounting under the table, or wall mounted all possible for your audio system.



### 1 Tabletop set up

Set the amplifier on the table allows you get it closer to your PC, CD, MICs or other audio sources, and easier control of volume.



## (2) Under the desk

To save more table area, you can also attach the amplifier under the desk with mounting kit in the packaging.

# Mounting on wall

Set the amplifier to another place if not need change frequently, you can adjust the volume with remote controller.





**COMMERCIAL AUDIO SYSTEM** 



### **Features**

- Small and compact design PA amplifier 50W;
- 100V mixer amplifier with 2 XLR microphone inputs,
- 2 aux inputs and 1 audio line output;
- Volume control of treble, bass, Mic1, Mic2, aux1, aux2, master volume;
- Remote control volume up and down from 10~ 30 meters distance;
- Support tabletop set, under desk or wall mounting way for installation;
- Full protection of thermal, shortcircuit and overload







#### Specification

Model No.	PA-500R
Rated Power	50W
Speaker Output	70V, 100V, 8Ω
Mic Sensitivity	Mic1/2: -50 dB bal XLR Imp 20KΩ
AUX Sensitivity	AUX1/2:-30dB unbal RCA Imp $10K\Omega$
Frequency Response	60~18KHz (±3 dB)
T.H.D	< 0.5% (at 1/3 rated power)
S/N Ratio	Mic: 70 dB / AUX: 80 dB
Antenna Connector	SMA-J / 50Ω (Cord Length 3M)
Weight	5.2 kg
Dimension	248 x 180 x 70 mm
Power Supply	AC 220~240V 50/60Hz





















